

IP-2BL-F36-DC

2MP Full Color HD IR Fixed Bullet
Network Camera



Features

- 2MP Full Color Fix Bullet IP Camera
- 1/2.8" Progressive CMOS, WDR, MIC, MicSD(Up to 256GB), Metal

Specifications

Video	
Imaging Device	1/2.7"
Effective Pixels	2MP1920(H)×1080(V)
Scanning System	Progressive CMOS
Min. Illumination	Color 0.05lux @ F1.2(AGC ON) ; B/W 0 lux @ IR ON
Lens Type	
Focal Length (Zoom Ratio)	3.6mm
Max. Aperture Ratio	F No. 1.0
Angular Field of View	H:88.88° V: 48.25° D: 105.59°
Min. Object Distance	1m
Lens Type	Fixed(M12)

Operational	
IR LED	2
WarmLight	2
IR Viewable Length	Up to 30m
WarmLight Viewable Length	Up to 25m
Type of complementary light	Default warm light, switchable infrared light
Camera Title	On/Off
Image Setting	Full Color Mode/Day&Night Mode/Schedule
Backlight Compensation	Off/On (5 Zone)
Wide Dynamic Range	DWDR
Digital Noise Reduction	3D DNR
Motion Detection	Off/On (8 Level)
Gain Control	Auto
White Balance	Auto/Manual
Electronic Shutter Speed	1/5 ~ 1/20000s
Flip / Mirror	Flip/Rotation
Alarm	NA
Audio	Built-in microphone
Hardware Reset	Yes
Smart Feature	NA
Network	
Ethernet	RJ45(10/100BASE-T)
Video Compression Format	H.265/H.264
Max. Resolution	Main Stream 1080P(1920x1080) Sub Steam VGA(640x480)
Video Quality Ajustment	128Kbps ~ 4Mbps
Bitrate control method	CBR/VBR
Streaming Capability	Dual-Stream(Main/Sub)
IP	IPv4

Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP,SMTP,NTP,UPnP,SNMP,HTTPS,FTP
Security	IP address filter;complicated password;Authenticated username and password
Streaming Method	Unicast/Multicast
Application Programming Interface	ONVIF
Web Viewer	IE8,9,10,11, Chrome 44/lower, Firefox 51/lower, Safari 11/lower,
Environmental	
Operating Temperature / Humidity	-30 ~ +60°C/less than ≤ 95% RH
Ingress Protection	IP66
Electrical	
Input Voltage / Current	D12V/POE(IEEE802.3af)
Power Consumption	5.04W
Mechanical	
Color / Material	White/Metal

Dimensions

