

NVR-S4/4P-1NA
4PoE 1SATA Network Video Recorder



Features

- 4ch channel PoE
- 1SATA HDD support up to 8TB
- Recording Bandwidth Max 50Mbps
- 8MP,5MP, 3MP ,2MP(1080P),1.3MP(960P),1.0MP(720P)
- 4K:45fps 4MP:90fps 2MP:180fps

Specifications

Model Name		NVR-S4/4P-1NA
Video	Resolution	8MP,5MP, 3MP ,2MP(1080P),1.3MP(960P),1.0MP(720P)
Recording Bandwidth	Inputs	50Mbps
	out	64Mbps
Performance		
Installation wizard		Yes
Live/Playback	Compression	Audio: G.711a Video : H.264/H.265
	Frame rate	4K:45fps 4MP:90fps 2MP:180fps
	AI	Yes
	Event	MD(Sensitivity Level 1~8) Videlo loss Beep, Email, Push notification to Mobile APP

	Playback function	Fast forward / backward (2x, 4x, 8x,16x) Slow forward (1/2x, 1/4x, 1/8x,1/16x)
	Playback	Max 4CH playback
UI/Monitoring	Local	UI5.0
	WEB	IE10/11 Safari V12.1 above Firefox V.52 above Google chrome V.57 above Edge V.79 above
	Mobile viewer	Rxcamview
	Push N/Atification	TUTK/RS
Interface		
P/W Reset		Factory Reset : Press 10 seconds
Monitors	VGA	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080)
	HDMI	1 (1024*768, 1280*720, 1280*1024, 1440*900, 1920*1080 , 2560*1440, 3840*2160/EDID)
Connections	POE	4POE
	Ethernet	1 RJ45 10/100 Base-T
	USB	USB2.0*1(front) USB2.0*1+(rear)
	Audio out	1
	E-sata	1 optional, not supported by default
	HDD	Software design can support up to 10T 1/2/3/4/6 T use 48V/1.2A (Design reserved 2HDD or 1HDD+1ESATA)
	Line in	1 optional, not supported by default
	RS485	1 optional, not supported by default
	Alarm Input/out	4 in /1 out optional, not supported by default
General		
OSD Language		More
Mechanical design	Dimension (WxDxH)	300X227X53mm
Electrical	Input Voltage/Current	1HDD:DC48V/1.2A 2HDD:DC48V/2A PoE Swith :48V
	Power consumption (excluding hard disk)	4W
Environmental	Operating Temperature	Temperature : 0°C~+40°C (32°F ~ 104°F)
	Humidity	Humidity : Less than 90%RH

Interfaces

